

Category Description

Water coolers

Pressure water cooler





Optional Water Filter





Filter Head VB-2

- Built-in valve allows cartridge change outs without shutting off the incoming water supply.
- 1/4" quick connect connections are compatible with plastic tubing Cartridge AP2-C405SG
- Removes Chlorine, Bad taste and Odour, Benzine Toxaphene and Dichlorobenzene and Reduces Sediment, Cysts and Lead
- Filtration level below 0.5 Micron.

Technical features

- External casing in stainless steel
- Stainless steel fountain top tested splash resistant equipped with mechanical pushbutton control jet and glass filler
- Cooling unit made from stainless steel both the tank and the refrigerant tube
- Fan cooled condenser copper tube with aluminum fins

Technical Specifications

Cold water production (Lt/h)	28	
Compressor power (HP)	1/5	
Dimensions (wxdxh σε mm)	320 x 320 x 1000	
Weight(Kgr)	25	
Water outlet temperature (°C)	8-12	
Power (W)	140	
Voltage (V/Hz) Other voltage upon request	220-240/50	

WATER INLET TEMPERATURE 20°C- ROOM TEMPERATURE 25°C

Installation guides

Water inlet	Drain	Electric cable
1/2´´ Bsp male thread	Flexible tube 3/4"	1,2m shuko plug

